

SECTION 10 51 29
DESIGN-TEC® LOCKERS
MANUFACTURED BY
SPEC-RITE DESIGNS, LLC
(SOLID PHENOLIC LOCKERS)

Specifier Note: This product guide specification must be reviewed and edited to meet the project requirements, building codes, and to select product options. This section includes Design-Tec® solid phenolic lockers and benches as manufactured by Spec-Rite Designs, LLC. Consult with the Spec-Rite Designs' Engineers for assistance in editing this specification for specific applications.

Part 1-General

1.01 Summary

Specifier Note: Design-Tec® lockers are fabricated from solid phenolic flat panels based on resin saturated cellulose fibers manufactured under high pressure and temperature. The decorative surface is applied to the core manufacturing process. The panel differs from HPL products because the core and surface are homogeneous and not glued to a core. Solid phenolic composite material resists moisture, graffiti, and chemicals.

- A. Section includes:**
Design-Tec® solid phenolic lockers
Design-Tec® solid phenolic benches

Specifier Note: The following section refers to products that match Design-Tec's aesthetic and performance characteristics and are typically required for similar applications and environments.

- B. Related Sections:**
10 21 13 DesignRite® phenolic toilet partitions
10 26 23 Wall Protection/Wall Lining phenolic
12 35 53 DesignLine® phenolic casework
12 35 53 Durable Designs® phenolic furniture
12 36 50 Laboratory Work Surface Tops phenolic

1.02 Submittals

- A. Submittals:** Comply with procedures and quantities as indicated in Division 1 Submittal Procedure Section.
- B. Shop Drawings:** Submit shop drawings indicating room sizes, layout, locker dimensions, material thickness, trim, hardware, finishes, locks, base, doors, accessories, and installation details.

- C. **Product Data:** Submit manufacturer's technical data for materials, fabrication, finishing, fastenings, hardware, and installation details.
- D. **Samples:** Submit samples of edge details, colors, patterns, finishes, and textures.
- E. **Closeout Documents:** Submit the following:
 - 1. Operation and Maintenance data
 - 2. Warranty

1.03 Quality Assurance

A. **Qualifications:**

- 1. Fabricator shall have 15 years or more experience in fabrication of solid phenolic materials and shall be experienced in performing work of similar size and scope.
- 2. Fabricator shall be capable of providing field service representation.
- 3. Installer shall be approved by the manufacturer and be experienced in performing work of similar size and scope.

- B. **Pre-installation Meeting:** Conduct pre-installation meeting (_____) weeks prior to installation to verify project requirements and conditions.

1.04 Delivery, Storage and Handling

- A. **Ordering:** Comply with supplier's ordering and lead-time guidelines to avoid delays.
- B. **Delivery:** Deliver materials in the manufacturer's original protective packaging.
- C. **Storage and Handling:** Store materials in an enclosed shelter providing protection from damage, temperature, humidity, and exposure to the elements.

1.05 Coordination and Project Conditions

- A. **Field Measurements:** Before material fabrication, verify actual field measurements and show actual measurements on shop drawings.
- B. **Coordination:** Coordinate field measurements with fabrication schedule construction progress to avoid construction delays.

1.06 Warranty

- A. Submit executed copy of the Spec-Rite Designs 15-year warranty against defects in material and 2 years against workmanship signed by an authorized representative of Spec-Rite Designs.

Part 2 – Products

2.01 Solid Phenolic Lockers

Spec-Rite Designs, LLC
1054 Central Industrial Drive
St. Louis, MO 63110
Phone: 314-633-4978
Fax: 314-771-7136
Email: info@specritedesigns.com
www.specritedesigns.com

A. Basis of Design: Drawings and specifications are based on Design-Tec Lockers.

B. Manufacturer and Fabricator:

Spec-Rite Design, LLC
1054 Central Industrial Drive
St. Louis, MO 63110
Phone: 1-877-249-6864 - Fax: (314) 771-7136
Email: info@specritedesigns.com

C. Model: Design-Tec fabricated from solid phenolic composite material.

2.02 Materials

A. Panel Material:

1. Decorative papers impregnated with the melamine resin on faces with a clear protective overcoat and integrally compression molded within a core consisting of solid phenolic impregnated kraft papers.

Specifier Note: Panel Material is available in Class B or Class A fire rating (ASTM E 84). Select from either option. Class A is available made to order at extended lead time.

2. Core or panel material shall meet fire resistance per ASTM E84 (Class B) (Class A).

3. Colors:

a. Doors and Ancillary Panels: (Manufacturer's standard stocking color collection range) (Manufacturer's full color range – extended lead time color collection).

1. Black Core
2. Natural/Brown Core
3. Color-Thru

b. Locker Interior: (Manufacturer's standard stocking color collection range) (Manufacturer's full color range – extended lead time color collection).

1. Black Core
2. Natural/Brown Core
3. Color-Thru

Specifier Note: Locker components are available in a wide range of colors at extended lead time. A standard stocking range is available in a shorter lead time. Consult with the manufacturer to avoid construction delays.

B. Doors:

1. **Material:** 1/2" (13mm) thick solid phenolic composite material.

2. **Corners:** Rounded

3. **Edges:** Crescent profile; machine polished and free from tooling imperfections

4. **Limit Arm:** Provide stainless steel limit arm to allow maximum opening to 90 degrees.

Specifier Note: Doors can be attached to hinge through-bolting (standard) or blind fixing (optional). Through-bolting is recommended for vandal-prone and high traffic areas. Blind fixing is recommended only for light duty areas where vandalism is not of concern.

5. Door Fastening: (Through Bolted) (Blind Fixing).

C. Locker Bodies:

- 1. Exposed edges:** Straight profile; eased edges to remove sharpness; machine polished and free from tooling imperfections.
- 2. Tops, bottoms, and intermediate shelves:** 1/2" (13mm) thick solid phenolic composite material with ventilation holes.
- 3. Locker backs:** 1/4" (6 mm) thick solid phenolic composite material.
- 4. Locker sides:** 3/8" (10 mm) thick solid phenolic composite material.

Specifier Note: Locker bodies are modular and can stand alone as a single unit. Locker body side panels have exposed fasteners. Applied finished end panels conceal fasteners when locker side is visible from the layout conditions. Filler panels enclose exposed fasteners when locker side meets a corner or wall. Finished end panels and/or filler panels are required for a finished installation.

D. Ancillary Panels: Finished end panels and closures shall be 1/2" (13mm) thick solid phenolic composite material.

E. Hardware:

- 1. Hinges:**
 - a. Material: 304-grade stainless steel.
 - b. Quantity: Three (3) for full height doors and two (2) for multi-tier units.
- 2. Interior hooks:**
 - a. Material: Stainless Steel.
 - b. Top Hook: Two prong: one per opening for 1 Tier, 2 Tier, and Z-Type.
 - c. Side Hook: Single prong: two per opening for 1 Tier, 2 Tier, and Z-Type.
- 3. Retaining Bar:** Provide stainless steel limit arm opening no more than 90 degrees.
- 4. Fasteners:** Exposed fasteners shall be 304 stainless steel.
- 5. Fastener Application:** Apply directly into or through the material.
- 6. Other Reinforcement:** Aluminum or metal profiles for reinforcements shall not be permitted.
- 7. Door Identification (identification plates):** See Section 2.04 C.

F. Ventilation:

- 1. Interior Vent:** Provide six 3/8" (10mm) diameter ventilation holes on tops, bottoms, and intermediate shelves. Provide three 3/8" (10mm) diameter ventilation holes on Z-Type intermediary shelves.

2. Door Vent: Provide minimum of 20 squares inches opening of front ventilation for full tier 12" wide x 72" high. For other styles, provide front ventilation 1.43 square inches per lineal foot of door perimeter.

G. Base:

Specifier Note: Edit this paragraph to indicate curb type(s) and indicate on plans.

1. Base not furnished with Locker: (Curb mounted) (_____)
2. Base furnished with locker: Adjustable leg mounted: 3-3/4" adjustable to 5-1/2", ABS plastic mounting-leveling leg.

2.03 Size

Specifier Note: Indicate locker size(s). Each locker "frame" is modular and includes the overall height of the locker (less the curb). Consult manufacturer for custom sizes.

- A. **Number of Doors:** (1) (2) (3) (4) (5) (6) (2, Z-Type)
- B. **Overall Height:** (59-3/4") (71-3/4") (_____)
- C. **Overall Width:** (12") (15") (18") (24") (_____)
- D. **Overall Depth:** (12-3/8") (15-3/8") (18-3/8") (20-3/8") (24-3/8") (_____)

2.04 Accessories and Options

Specifier Note: Select required accessories and delete items not required. Consult manufacturer for accessory recommendations.

Specifier Note: Choices of locking options are available to meet the various needs of locker users. Consult with manufacturer for lock selection recommendation. Specify lock selection(s) and indicate on plans where applicable.

- A. **Locking System:** (Hasp preparation for padlock) (Kenstan® spring-bolt key lock) (Medeco® (high security) key locks) (MasterLock® built-in combination lock) (Digilock®) (Real Lock®) (_____).

Specifier Note: Sloping tops are optional, flat tops are standard and are included as part of the locker body. Specify sloped or flat tops.

- B. **Locker Top:** 1/2" top shall be (Flat] (Sloped width 1/4 " (6mm) thick solid phenolic composite material).
- C. **Door Identification:** Fonts to be a minimum 1/2" high and up to four alphanumeric characters. Numbering sequence to be provided by architect.

1. Stainless steel with black engraved numbers surface mounted with permanent adhesive integral with the locking mechanism.
2. Black plastic with white engraved numbers surface mounted with permanent adhesive integral with the locking mechanism.
3. Stainless Steel Disk 1-1/2" diameter attached with permanent adhesive.
4. Brushed Aluminum Disk 1-1/2" diameter attached with permanent adhesive.
5. Brass Disk 1-1/2" diameter attached with permanent adhesive.

- D. Hang Rod:** Chrome plated zinc, galvanized, cadmium-coated steel.
- E. Additional Door Ventilation:** (Holes through door in (diamond) (circle) pattern) (_____).
- F. ADA Accessibility Options:**

Specifier Note: Consult building codes and determine requirements for accessibility.

- ADA
1. Shelf Kit: Shelf kit can be utilized to meet reach range requirements.
 2. Door Kit: Door kit shall include additional door handle to meet door pull requirements and shall include handicap signage (Routed ADA logo or adhesive backed signage.)
 3. Where lockers are provided in accessible spaces, at least (five percent (5%)) (_____) but not less than (one (1)) (_____), of each type of locker shall comply with accessibility guidelines.

2.05 Solid Phenolic Benches

Specifier Note: Edit this paragraph to indicate bench type(s) or delete as required.

- A. Non-integrally mounted:**
1. H-Frame: 2" x 2" black powder coated aluminum frame, adjustable from 18" to 22" high, with minimum of 1/2" thick bench top.
 2. Pedestal Mounted: 2" x 2" black powder coated aluminum frame, 18" high, with 3/4" thick bench top.
 3. Wall Mounted: Black powder coated aluminum brackets with 3/4" thick, 12" wide bench top.
- B. Integrally mounted:** 3/4" thick solid phenolic composite material cantilevered from (locker H-Frame base) (_____) with black powder coated aluminum supports.

Part 3 – Execution

3.01 Examination

- A.** Examine site conditions before locker installation. Notify architect of unacceptable areas. Do not install locker until unacceptable conditions have been corrected.

3.02 Installation

- A. Install lockers in locations as shown on shop drawings per manufacturer's instructions.
- B. Install lockers plumb, level, square, rigid, and flush.
- C. Install all required trim, fillers, end panels, and closures per manufacturer's instructions.
- D. Use hardware supplied or recommended by the manufacturer.
- E. Attach number plates to doors as indicated on shop drawings.
- F. Correct and/or replace damaged components as directed by architect.

3.03 Adjustment

- A. Adjust doors and locks for smooth operation without binding.
- B. Lubricate door hinges and locks per manufacturer's instructions.

3.04 Cleaning

- A. Clean all surfaces in accordance with manufacturer's instructions.
- B. Do not use abrasive cleaners.

End of Section